SAFETY AUDIT CHECKLIST

Fixed Industrial Stairs

Check the box under Y for "yes" or N for "no" to determine if each item is within compliance. Y N 1. Are fixed stairs provided for access from one structure level to another where operations necessitate regular travel between levels, and for access to operating platforms? any equipment which requires attention routinely during operations? 1910.24(b) 2. Are fixed stairs provided where access to elevations is daily or at each shift for such purposes as aguing, inspection, regular maintenance, etc., where such work may expose employees to acids, caustics, gases, or other harmful substances, or for which purposes the currying of tools or equipment by hand is normally required? 1910.24(b) 3. Are spiral stairways not permitted except for special limited usage and secondary access situations where it is not practical to provide a conventional stairway? 1910.24(b) 3. For winding stairways installed on tanks and similar round structures, is the diameter of the structure not less than 5 feet? 1910.24(b) 3. For winding stairways and similar ound structures, is the diameter of the structure not less than 5 feet? 1910.24(c) 3. For winding stairways and similar round structures, is the diameter of the structure not less than 5 feet? 1910.24(c) 4. For winding stairways and similar round structures, is the diameter of the structure not less than 5 feet? 1910.24(c) 5. Are fixed stairis vasafled an angles to the horizontal of between 30 degrees and 50 degrees; 1910.24(c) 9. For winding stairway and suminimum width of 22 inches? 1910.24(c) 10. Are stairway platforms no less than the width of a stairway platforms no less than the width of a stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of Inavel? 1910.24(f)	Audited by:	Date:	
1. Are fixed stairs provided for access from one structure level to another where operations necessitate regular travel between leveles, and for access to operating platforms at any equipment which requires attention routinely during operations? 1910.24(b) 2. Are fixed stairs provided where access to elevations is daily or at each shift for such purposes as gauging, inspection, regular maintenance, etc., where such work may expose employees to acids, caustics, gases, or other harmful substances, or for which purposes the carrying of tools or equipment by hand is normally required? 1910.24(b) 3. Are spiral stairways not permitted except for special limited usage and secondary access situations where it is not practical to provide a conventional stairway? 1910.24(b) 5. Are fixed stairways designed and constructed to carry a load of 5 times the normal live load anticipated but never of less strength than to carry safely a moving concentrated load of 1,000 pounds? 1910.24(c) 6. Do fixed stairways have a minimum width of 22 inches? 1910.24(d) 7. Are fixed stair installed at angles to the horizontal of between 30 degrees and 50 degrees? 1910.24(c) 8. Are all treads reasonably slip-resistant and are the nosings of nonship finish? 1910.24(e) 9. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	Check the box under Y for "yes" or N for "no" to determine if each item is within compliance. Item # Repair D		
one structure level to another where operations necessitate regular travel between levels, and for access to operating platforms at any equipment which requires attention routinely during operations? 1910.24(b)	<u>Y</u> <u>N</u>	<u> </u>	
□ 2. Are fixed stairs provided where access to elevations is daily or at each shift for such purposes as gauging, inspection, regular maintenance, etc., where such work may expose employees to acids, caustise, gases, or other harmful substances, or for which purposes the carrying of tools or equipment by hand is normally required? 1910.24(b) □ 3. Are spiral stairways not permitted except for special limited usage and secondary access situations where it is not practical to provide a conventional stairway? 1910.24(b) □ 4. For winding stairways installed on tanks and similar round structures, is the diameter of the structure not less than 5 feet? 1910.24(b) □ 5. Are fixed stairways designed and constructed to carry a load of 5 times the normal live load anticipated but never of less strength than to carry safely a moving concentrated load of 1,000 pounds? 1910.24(c) □ 6. Do fixed stairways have a minimum width of 22 inches? 1910.24(d) □ 7. Are fixed stairs installed at angles to the horizontal of between 30 degrees and 50 degrees? 1910.24(e) □ 9. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) □ 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	one structure level to another where opera- tions necessitate regular travel between lev- els, and for access to operating platforms at any equipment which requires attention rou-	sides of all exposed stairways and stair platforms? 1910.24(h) 12. Are handrails provided on at least one side of closed stairways preferably on the right	
for special limited usage and secondary access situations where it is not practical to provide a conventional stairway? 1910.24(b) 4. For winding stairways installed on tanks and similar round structures, is the diameter of the structure not less than 5 feet? 1910.24(b) 5. Are fixed stairways designed and constructed to carry a load of 5 times the normal live load anticipated but never of less strength than to carry safely a moving concentrated load of 1,000 pounds? 1910.24(c) 6. Do fixed stairways have a minimum width of 22 inches? 1910.24(d) 7. Are fixed stairs installed at angles to the horizontal of between 30 degrees and 50 degrees? 1910.24(e) 8. Are all treads reasonably slip-resistant and are the nosings of nonslip finish? 1910.24(e) 9. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	elevations is daily or at each shift for such purposes as gauging, inspection, regular maintenance, etc., where such work may expose employees to acids, caustics, gases, or other harmful substances, or for which purposes the carrying of tools or equipment	□ □ 13. Is the vertical clearance above any stair tread to an overhead obstruction at least 7 feet measured from the leading edge of the tread? 1910.24(i)	
and similar round structures, is the diameter of the structure not less than 5 feet? 1910.24(b) S. Are fixed stairways designed and constructed to carry a load of 5 times the normal live load anticipated but never of less strength than to carry safely a moving concentrated load of 1,000 pounds? 1910.24(c) O. Do fixed stairways have a minimum width of 22 inches? 1910.24(d) T. Are fixed stairs installed at angles to the horizontal of between 30 degrees and 50 degrees? 1910.24(e) Are all treads reasonably slip-resistant and are the nosings of nonslip finish? 1910.24(e) S. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	for special limited usage and secondary access situations where it is not practical to provide a conventional stairway?		
structed to carry a load of 5 times the normal live load anticipated but never of less strength than to carry safely a moving concentrated load of 1,000 pounds? 1910.24(c)	and similar round structures, is the diameter of the structure not less than 5 feet?		
of 22 inches? 1910.24(d) 7. Are fixed stairs installed at angles to the horizontal of between 30 degrees and 50 degrees? 1910.24(e) 8. Are all treads reasonably slip-resistant and are the nosings of nonslip finish? 1910.24(e) 9. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	structed to carry a load of 5 times the normal live load anticipated but never of less strength than to carry safely a moving con-		
horizontal of between 30 degrees and 50 degrees? 1910.24(e) 8. Are all treads reasonably slip-resistant and are the nosings of nonslip finish? 1910.24(e) 9. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)			+
are the nosings of nonslip finish? 1910.24(e) 9. Is rise height and tread width uniform throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	horizontal of between 30 degrees and 50		
throughout any flight of stairs including any foundation structure used as one or more treads of the stairs? 1910.24(f) 10. Are stairway platforms no less than the width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	are the nosings of nonslip finish?		
width of a stairway and a minimum of 30 inches in length measured in the direction of travel? 1910.24(f)	throughout any flight of stairs including any foundation structure used as one or more		
Notes:	width of a stairway and a minimum of 30 inches in length measured in the direction		
	Notes:		